

ADELAIDE

RWY	(CN)	TORA	TODA	ASDA	LDA
05	(4)	3100 (10170)	3204 (10512) (2.4%)	3160 (10367)	2950 (9678)
RWY 05 DTHR 150M.					
23	(4)	3100 (10170)	3204 (10512) (2.63%)	3160 (10367)	3100 (10170)
Aerial 16M FM CWY end and 2.8FT ABV CWY end not included in calculation of TODA GRAD and STODA.					
Slope 0.1% down to SW. RWY WID 45 RWS WID 280 Graded 150					
12	(4)	1652 (5420)	1832 (6010) (2.58%)	1652 (5420)	1652 (5420)
30	(4)	1652 (5420)	1832 (6010) (2.22%)	1652 (5420)	1652 (5420)
1. OBST limitation SFC not surveyed to ICAO standard					
2. Length of approach SFC 7500M. Length of TKOF SFC 7500M.					
Slope Level. RWY WID 45 RWS WID 280 Graded 150					

SUPPLEMENTARY TAKEOFF DISTANCES

RWY05-	2872(9422)(1.6)	3073(10082)(1.9)	3160(10367)(2.2)
RWY23-	2868(9409)(1.6)	3031(9944)(1.9)	3125(10253)(2.2) 3183(10443)(2.5)
RWY12-	1363(4472)(1.6)	1616(5302)(1.9)	1728(5669)(2.2) 1813(5948)(2.5)
RWY30-	1514(4967)(1.6)	1745(5725)(1.9)	1831(6007)(2.2)

TAXIWAY INTERSECTION DECLARED DISTANCES

RWY05-	TKOF from TWY E2; RWY remaining 1555(5102)	reduce all DIST by 1545(5069)
RWY05-	TKOF from TWY F4; RWY remaining 2076(6811)	reduce all DIST by 1024(3360)
RWY05-	TKOF from TWY F5; RWY remaining 2427(7963)	reduce all DIST by 673(2208)
RWY23-	TKOF from TWY D1; RWY remaining 2180(7152)	reduce all DIST by 920(3018)