




GNSS ARRIVAL PROCEDURES HORN ISLAND, QLD (YHID) Page 1

27 FEB 2020

AWIS 122.125	FIA BN CEN 120.3	CTAF+AFRU 126.5	AFRU+PAL 126.5		Bearings are Magnetic Elevations in FEET AMSL
-----------------	---------------------	--------------------	-------------------	--	--

25 NM MSA
2400
HID NDB
2000
B-165°
B-216°

REFERENCE WAYPOINT HID NDB

HID NDB 356

AD ELEV 43

* NO CIRCLING IN SECTOR SOUTH OF RWY 26 AND EAST OF RWY 32.
LANDING NOT PERMITTED RWY 32.

10 NM MSA 2000

SECTOR A

MISSED APPROACH:
CLIMB ON TRACK TO 2400FT.

NM TO NDB	25	16	7	5	4	0									
CIRCLING MINIMA	A,B: 970-2.4		C: 1030-4.0		D: N/A										
NM TO NDB	5.1	5	4	3	2.1	2	1.8								
ALT (3° APCH PATH)	2000	1970	1650	1330	1030	1010	970								

SECTOR B

MISSED APPROACH:
CLIMB ON TRACK TO 2000FT.

NM TO NDB	25	15	9	5	0										
CIRCLING MINIMA	A,B: 970-2.4		C: 1030-4.0		D: N/A										
NM TO NDB	7.2	7	6	5	4	3	2.9	2.7							
ALT (3° APCH PATH)	2400	2340	2020	1700	1380	1060	1030	970							

SECTOR C


MISSED APPROACH:
CLIMB ON TRACK TO 2000FT.

NM TO NDB	25	15	6	5	0										
CIRCLING MINIMA	A,B: 1000-2.4		C: 1030-4.0		D: N/A										
NM TO NDB	5.8	5	4	3	2.8	2.7									
ALT (3° APCH PATH)	2000	1750	1430	1110	1030	1000									

Changes: CAT C MINIMA, SECTOR B MIN ALT, DIST/ALT. HIDDG01-162

GNSS ARRIVAL PROCEDURES HORN ISLAND, QLD (YHID) Page 2



27 FEB 2020



USE QNH

RNP RWY 08

7 SEP 2023

HORN ISLAND, QLD (YHID)**NOTES**

CATEGORY	A	B	C	D
LNAV/VNAV	540 (528-3.0)			NOT APPLICABLE
LNAV	690 (678-3.9)			
CIRCLING *	970 (927-2.4)		1030 (987-4.0)	
ALTERNATE	(1427-4.4)		(1487-6.0)	

1. MAX IAS:
INITIAL : 210KT.
- * 2. NO CIRCLING IN
SECTOR SOUTH OF
RWY 26 AND EAST
OF RWY 32.
3. LANDING NOT
PERMITTED RWY 32.

Changes: WPT NAMING CONVENTION, MIN ALT.


HIDGN01-176

USE QNH

RNP RWY 26

HORN ISLAND, QLD (YHID)


7 SEP 2023



NM TO NEXT WPT	RW26	1.9	2.4	3	4	HI2EF	1	2.3						
ALT (3° APCH PATH)		670	830	1030	1350	1670	1980	2400						

MISSED APPROACH:

TRACK DCT TO HI2EH,
TURN RIGHT TRACK 056°,
CLIMB TO 2400FT.

**NOTES**

1. MAX IAS:
INITIAL : 210KT.
- * 2. NO CIRCLING IN
SECTOR SOUTH OF
RWY 26 AND EAST
OF RWY 32.
3. LANDING NOT
PERMITTED RWY 32.
4. VERTICAL PATH NOT
ALIGNED WITH PAPI
RWY 26.

CATEGORY	A	B	C	D
LNAV/VNAV	670 (647-3.7)			NOT APPLICABLE
LNAV	830 (807-4.6)			
CIRCLING *	970 (927-2.4)		1030 (987-4.0)	
ALTERNATE	(1427-4.4)		(1487-6.0)	


Changes: WPT NAMING CONVENTION.

HIDGN02-176


USE QNH

NDB RWY 08
HORN ISLAND, QLD (YHID)

7 NOV 2019



DME DIST				NOT APPLICABLE					
ALT									



CATEGORY	A	B	C	D
S-I NDB	930 (918-5.0)			NOT APPLICABLE
CIRCLING *	970 (927-2.4)		1030 (987-4.0)	
ALTERNATE	(1427-4.4)		(1487-6.0)	



- NOTES**
- MAX IAS:
INITIAL :
CAT A&B 140KT.
CAT C 210KT.
 - NO CIRCLING IN SECTOR SOUTH OF RWY 26 AND EAST OF RWY 32.
 - LANDING NOT PERMITTED RWY 32.

Changes: CAT C CIRCLING MINIMA, ALTERNATE CAT C MINIMA. HIDNB01-161

USE QNH

NDB RWY 14
HORN ISLAND, QLD (YHID)

7 SEP 2023



CATEGORY	A	B	C	D
S-I NDB	970 (962-5.0)			NOT APPLICABLE
CIRCLING *	970 (927-2.4)		1030 (987-4.0)	
ALTERNATE	(1427-4.4)		(1487-6.0)	

Changes: CAUTION NOTE.

HIDNB02-176