

KING ISLAND

RWY	(CN)	TORA	TODA	ASDA	LDA
10	(3)	1585 (5200)	1645 (5397) (2.46%)	1585 (5200)	1585 (5200)
		OBST fence 108FT AMSL BRG 101 MAG 911M FM ARP not taken into account in calculation of TODA GRAD and STODA.			
28	(3)	1585 (5200)	1645 (5397) (1.2%)	1585 (5200)	1585 (5200)
		OBST fence 130FT AMSL BRG 297 MAG 894M FM ARP not taken into account in calculation of TODA GRAD and STODA.			
		Slope 0.33% down to the W and 0.45% down to the E. Highest point 660M FM W end. RWY WID 30 RWS WID 150 Graded 90			
17	(2)	1105 (3625)	1165 (3822) (3.87%)	1105 (3625)	1105 (3625)
35	(2)	1105 (3625)	1165 (3822) (3.44%)	1105 (3625)	1105 (3625)
		Slope 0.9% down to N. RWY WID 30 RWS WID 90			

SUPPLEMENTARY TAKEOFF DISTANCES

RWY10- 1307(4288)(1.6) 1465(4806)(1.9) 1588(5210)(2.2)

RWY17- 1068(3504)(2.2) 1119(3671)(2.5) 1152(3779)(3.3)

RWY35- 1057(3468)(1.6) 1083(3553)(1.9) 1104(3622)(2.2) 1124(3688)(2.5) 1160(3806)(3.3)