

MELBOURNE/ESSENDON

| RWY | (CN) | TORA | TODA | ASDA | LDA |
|------------|-------------|-------------|---------------------|-------------|-------------|
| 08 | (4) | 1921 (6302) | 1981 (6499) (2.57%) | 1921 (6302) | 1921 (6302) |
| 26 | (4) | 1921 (6302) | 1981 (6499) (4.14%) | 1921 (6302) | 1921 (6302) |

1. OBST in flyover area of RWS refer ERSA.

2. Multiple lit and unlit masts BTN 2061-2204M FM RWY 26 SOT BTN 101M L and 101M R RCL.

3. Masts infringe 2% TKOF SFC up to 3.3% not ABV 261FT AMSL.

4. Masts are street lights along the Tullamarine Freeway.

Slope 0.4% down to the W for 700M then 0.2% down to E for the remainder. RWY WID 45 RWS WID 180 Graded 150

| | | | | | |
|----|-----|-------------|---------------------|-------------|-------------|
| 17 | (3) | 1503 (4931) | 1563 (5128) (3.06%) | 1503 (4931) | 1503 (4931) |
| 35 | (3) | 1503 (4931) | 1563 (5128) (1.81%) | 1503 (4931) | 1503 (4931) |

RWY 35 fixed distance and touch down zone markings displaced 33M to N.

Slope 0.9% down to S. RWY WID 45 RWS WID 150

SUPPLEMENTARY TAKEOFF DISTANCES

RWY08- 1908(6260)(1.6) 1936(6352)(1.9) 1958(6424)(2.2) 1975(6480)(2.5)

RWY26- 1639(5377)(1.6) 1716(5630)(1.9) 1775(5823)(2.2) 1822(5978)(2.5) 1910(6266)(3.3)

RWY17- 1429(4688)(1.6) 1472(4829)(1.9) 1501(4924)(2.2) 1528(5013)(2.5)

RWY35- 1310(4298)(1.6)