


**BARROW ISLAND****ELEV 24****AVFAX CODE 6803**

WA  
205152S 1152422E UTC +8 YBWX  
VAR 1 DEG E CERT  
AD OPR Aerodrome Management Services Pty Ltd, PO Box 6127, East Perth,  
WA, 6892. Email: bwairport@chevron.com. PH AD Manager 08 9184 3789.

**REMARKS**

1. Restricted OPS. PPR from AD OPR.
2. ALL OPS - Advise AD OPR at least 20 MIN prior to ETA on 131.25.

**HANDLING SERVICES AND FACILITIES**

Marshalling, parking allocation and ground handling services by prior arrangement with AD OPR.

Viva Energy Australia – JET A1 only. VIVA Carnet card or contract arrangement.

**PASSENGER FACILITIES**

LG/RF/WC/Telephone facilities AVBL and Telstra 3G mobile reception.

**APRONS AND TAXIWAYS**

1. All ACFT to follow APN markings.
2. Dual Lead-out lines on PRKG bays 2-4.
  - a. Inner Leads-outs for: Q400, B463 and F100
  - b. Outer Leads-outs for: Q400, E190 and F100
3. All jet ACFT to use idle power for movements on the APN with the exception of breakaway thrust to initiate taxi. ACFT that cannot comply with this restriction must advise AD OPR prior to departure.

**AERODROME OBSTACLES**

1. Towers:
  - a. 584FT AMSL, BRG 343 MAG 2.7NM FM ARP, infringes conical SFC by 404FT, lit H24, HIOL strobe HJ, steady red MIOL HN.
  - b. 246FT AMSL BRG 343 MAG 2.7NM FM ARP infringes conical SFC by 75FT, marked and lit steady red MIOL HN.
  - c. 629FT AMSL BRG 345 MAG 2.77NM FM ARP infringes conical SFC by 445FT marked orange and white and lit by flashing red MIOL HN.
2. Primary IWI 41FT AMSL BRG 238 MAG 0.3NM FM ARP infringes transitional SFC by 5FT.

**METEOROLOGICAL INFORMATION PROVIDED**

1. TAF CAT B, METAR/SPECI.
2. AWIS PH 08 6216 2602 - Report faults to BoM.
3. AWIS FREQ 132.150 (requires one-second pulse to activate) - Report faults to AD OPR.

**PHYSICAL CHARACTERISTICS**

03/21 026 62a PCN 25 / F / A / 1210 (175PSI) / T Grooved WID 30 RWS 150

**AERODROME AND APPROACH LIGHTING**

RWY 03/21	LIRL	AFRU+PAL 120.1		SDBY PWR AVBL
RWY 03/21	PAPI(1)	AFRU+PAL 120.1	3.0 DEG41FT	SDBY PWR AVBL
RWY 03/21	PTBL(2)			BY PRIOR
				ARRANGEMENT

- (1) Left side.
- (2) 90MIN RQ to setout lighting.
  1. RWY edge lighting spacing: 90M.
  2. Lighting manually activated by ARO 30MIN prior to scheduled ACFT arrival and deactivated 15MIN after departure.

**OTHER LIGHTING**

1. SDBY PWR switchover time: 25 SEC.
2. TWY LGT: Blue edge (TWY B only).

**ATS AND AERODROME COMMUNICATION FACILITIES**

FIA MELBOURNE CENTRE 122.4 2000FT

---

**LOCAL TRAFFIC REGULATIONS**

1. RWY 03/21: All fixed wing ACFT ABV 20,000KG must make MAX RAD turns at MNM speed at turning nodes to avoid SFC damage.
2. Rotary ACFT are permitted to perform MID RWY turns. To avoid SFC damage rotary ACFT must make MAX RAD turns utilising full RWY width.
3. All ACFT are required to backtrack on RWY centre line.
4. All ACFT to contact "Barrow Ramp" on 130.40 prior to entering ramp area for PRKG instructions.
5. TWY A not AVBL for ACFT ABV 20,000KG.
6. Night OPS – Code C ACFT PRKG Bay 3 only.

**FLIGHT PROCEDURES**

Right hand CCTS required when OPR on RWY 03.

**CTAF - AFRU** 120.1

**ADDITIONAL INFORMATION**

1. Bird hazard, significantly increased bird activity after dusk and after rainfall.
2. Plume rise SFC to 1,800FT AMSL BRG 026 DEG MAG, 5NM FM ARP.
3. Extensive HEL OPS conducted DLY at and WI AD VCY.

**CHARTS RELATED TO THE AERODROME**

1. WAC 3229.
  2. Also refer to AIP Departure and Approach Procedures.
-