


CARNARVON

AVFAX CODE 6501

ELEV 13



WA 245250S 1134020E UTC +8 YCAR
 VAR 0 DEG W CERT
 AD OPR Shire of Carnarvon, PO Box 459, Carnarvon, WA, 6701.
 Email: swao@carnarvon.wa.gov.au. ARO 08 9941 4135: 0419 041
 723. Council PH 08 9941 0000.

REMARKS

- AD Charges: All ACFT - Copy of charges AVBL from AD Supervisor.
- This AD is a Security Controlled Airport.
- High VIS clothing to be work on APN.
- Terminal only open one hour prior to RPT flights.

HANDLING SERVICES AND FACILITIES

World Fuel Services (WFS): 0800-1700 Local MON-FRI, PH 0418 911 465 (H24) or email: carnarvon@uafuel.com.au. H24 AVGAS bowser WFS cardswipe and credit card (via smartphone APP), AVGAS tanker, JET A1 tanker, PN essential.
 AIR BP: 2300-1000 UTC JO, AH 60MIN PN. Call-out fee applies AH. MOB 0429 923 227, JET A1, AVGAS H24 card bowser.
 Gascoyne Airport Services (baggage handling) - email: cpfletcher37@gmail.com.

PASSENGER FACILITIES

WC (AVBL H24 at rear of terminal)/TX Carnarvon Taxi Service phone 131 008 and Valli Taxis phone 0413 312 665. Mobile phone coverage by Optus and Telstra.

AERODROME OBSTACLES

- Levee banks 1,244M from SOT RWY 18 and 1,723M from SOT RWY 22.
- Unlit radio mast 142FT 347 DEG MAG 920M FM ARP.
- Lit mast 182FT AMSL BRG 359 DEG MAG 866M FM ARP. Infringes inner HZS by 29.5FT.
- Tank 85.3FT AGL BRG 236 DEG MAG 0.76NM FM ARP. Infringes transitional SFC by 6FT.

METEOROLOGICAL INFORMATION PROVIDED

- TAF CAT D, METAR/SPECI.
- AWIS Phone 08 6216 2605 - Report faults to BoM.
- AWIS FREQ 126.45 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

04/22	044	53a	PCN 13 /F /A /840 (122PSI) /U Sealed	WID 30	RWS 150
18/36	180	37a	PCN 13 /F /A /5700/700 (102PSI) /U Sealed	WID 30	RWS 90

AERODROME AND APPROACH LIGHTING

RWY 04/22 LIRL AFRU+PAL 126.7 SDBY PWR AVBL
 RWY edge light spacing: 04/22: 60M.

OTHER LIGHTING

- Secondary PWR switchover time: 10 SEC.
- TWY LGT: Blue edge.
- APN lighting - all bays: not compliant to MOS 139 for night OPS.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 122.1 On ground

RADIO NAVIGATION AND LANDING AIDS

DME	CAR	113.0/ 77X	245255.3S	1134022.9E		(1)
NDB	CAR	323	245312.3S	1134009.2E	Range 120 (HN 85)	
VOR	CAR	113.0	245255.3S	1134022.4E		

(1) Antenna ELEV 34FT.

Monitored by ML.

LOCAL TRAFFIC REGULATIONS

1. All ACFT greater than 5,700KG must turn at RWY THR.
2. ACFT ABV 5,700KG are permitted to taxi via RWY 18/36 to access TWY B.
3. **HELICOPTER OPERATIONS**
 - a. Departures/Arrivals
 - (i) During DEP HEL are to air taxi onto TWY for DEP on the RWY. DEP turns tracking toward the east only to be executed once clear of the circuit. No DEP to the east across the RWY should be executed.
 - (ii) Due to possible shielding effects FM ACFT hangars along south western edge of the general aviation APN, HEL TFC is to adhere to unmanned airfield PROC during ARR and DEP. The circuit is to be joined as per these PROC for the RWY to be used.
 - (iii) Skid mounted HEL not permitted on RPT apron.

CTAF - AFRU 126.7**ADDITIONAL INFORMATION**

Bird hazard exists HJ, flock of corellas on RWY 04/22 and RWY 18/36.

CHARTS RELATED TO THE AERODROME

1. WAC 3346.
 2. Also refer to AIP Departure and Approach Procedures.
-