

INVERELL

RWY	(CN)	TORA	TODA	ASDA	LDA
04	(1)	700 (2297)	730 (2395) (4.55%)	700 (2297)	700 (2297)
22	(1)	700 (2297)	730 (2395) (4.9%)	700 (2297)	700 (2297)
Slope 1.2% down to SW. RWY WID 18 RWS WID 60 Graded 60					
16	(3)	2114 (6936)	2174 (7132) (5.27%)	2114 (6936)	2114 (6936)
34	(3)	2114 (6936)	2174 (7132) (3.3%)	2114 (6936)	2114 (6936)

1. TODA end GRAD and STODA based on 180M TKOF inner edge width with 12.5% diversion splays.

2. APCH GRAD to THR 16 at N end is 3.30% and to THR 34 at S end is 3.0% for 150M APCH inner edge width with 15% diversion splays.

Slope Average 1.0% down to N and FM THR 34 down 0.64% for first 1329M and then down 1.55% to THR 16. RWY WID 30 RWS WID 150 Graded 90

SUPPLEMENTARY TAKEOFF DISTANCES

RWY16-	1726(5663)(1.6)	1912(6273)(1.9)	2022(6634)(2.2)	2104(6903)(2.5)	2140(7021)(3.3)
	2171(7123)(5.0)				
RWY34-	1914(6279)(1.6)	1973(6473)(1.9)	2023(6637)(2.2)	2173(7129)(2.5)	