

**MELBOURNE/ESSENDON**

<b>RWY</b>	<b>(CN)</b>	<b>TORA</b>	<b>TODA</b>	<b>ASDA</b>	<b>LDA</b>
08	(4)	1921 (6302)	1981 (6499) (2.57%)	1921 (6302)	1921 (6302)
26	(4)	1921 (6302)	1981 (6499) (4.14%)	1921 (6302)	1921 (6302)

1. OBST in flyover area of RWS refer ERSA.

2. Multiple lit and unlit masts BTN 2061-2204M FM RWY 26 SOT BTN 101M L and 101M R RCL.

3. Masts infringe 2% TKOF SFC up to 3.3% not ABV 261FT AMSL.

4. Masts are street lights along the Tullamarine Freeway.

Slope 0.4% down to the W for 700M then 0.2% down to E for the remainder. RWY WID 45 RWS WID 180 Graded 150

17	(3)	1503 (4931)	1563 (5128) (3.06%)	1503 (4931)	1503 (4931)
35	(3)	1503 (4931)	1563 (5128) (1.81%)	1503 (4931)	1503 (4931)

RWY 35 fixed distance and touch down zone markings displaced 33M to N.

Slope 0.9% down to S. RWY WID 45 RWS WID 150

**SUPPLEMENTARY TAKEOFF DISTANCES**

RWY08- 1908(6260)(1.6) 1936(6352)(1.9) 1958(6424)(2.2) 1975(6480)(2.5)

RWY26- 1639(5377)(1.6) 1716(5630)(1.9) 1775(5823)(2.2) 1822(5978)(2.5) 1910(6266)(3.3)

RWY17- 1429(4688)(1.6) 1472(4829)(1.9) 1501(4924)(2.2) 1528(5013)(2.5)

RWY35- 1310(4298)(1.6)