

PERTH

RWY	(CN)	TORA	TODA	ASDA	LDA
03	(4)	3444 (11299)	3504 (11496) (1.97%)	3444 (11299)	3444 (11299)
21	(4)	3444 (11299)	3644 (11955) (2.75%)	3444 (11299)	3444 (11299)

1. RWY 03/21: Transitional SFC infringed W side 300M FM RWY 03 THR. OBST is illuminated WDI 94FT AMSL.

2. OLS extensively infringed by terrain E of AD.

Slope 0.2% down to N. RWY WID 45 RWS WID 300 Graded 150

06	(4)	2163 (7096)	2224 (7296) (2.39%)	2163 (7096)	2163 (7096)
24	(4)	2163 (7096)	2224 (7296) (2.26%)	2163 (7096)	2163 (7096)

OLS extensively infringed by terrain E of AD.

Slope from THRs 0.1% down to centre. RWY WID 45 RWS WID 300 Graded 150

SUPPLEMENTARY TAKEOFF DISTANCES

RWY03- 3382(11096)(1.6) 3482(11424)(1.9)

RWY21- 3251(10666)(1.6) 3370(11056)(1.9) 3453(11329)(2.2) 3497(11473)(2.5)

RWY06- 1954(6411)(2.2)

RWY24- 1786(5860)(1.6) 2024(6640)(1.9) 2195(7201)(2.2)

TAXIWAY INTERSECTION DECLARED DISTANCES

RWY03- TKOF from TWY A7; RWY remaining 2035(6676) reduce all DIST by 1409(4623)

RWY03- TKOF from TWY A9; RWY remaining 2535(8317) reduce all DIST by 909(2982)

RWY03- TKOF from TWY C9; RWY remaining 2535(8317) reduce all DIST by 909(2982)

RWY21- TKOF from TWY D; RWY remaining 2680(8793) reduce all DIST by 764(2507)

RWY06- TKOF from TWY J1; RWY remaining 1819(5968) reduce all DIST by 344(1129)