

**FORTESCUE DAVE FORREST****ELEV 1563****AVFAX CODE 6830**

WA

UTC +8

YDFD


221731S

1192614E

VAR 1 DEG E

CERT

AD OPR Chichester Metals Pty Ltd, PO Box 6915, East Perth, WA, 6892. Email:  
cbairport@fmgl.com.au. PH AD Manager 08 9176 6038. ARO H24 0437 488 818.

**REMARKS**

PPR 24HR PN required for all unscheduled ACFT.

**HANDLING SERVICES AND FACILITIES**

Air BP JET A1 CTC AD Manager/ARO.

**General**

ACFT marshalling is provided for all ACFT ABV 5,700KG MTOW.

**AERODROME OBSTACLES**

- Terrain (hills) lit-LIOL, 1,769FT AMSL, BRG 330 MAG 2.6NM FM ARP.
- Extensive terrain penetration of inner HZS to 1,800FT AMSL in N quadrant, BRG 324 MAG to 052 MAG, 2NM to 2.92NM FM ARP.
- Boundary Fence, infringing transitional SFC by 2FT to 5.25FT AGL, offset 77M FM RWY CL.
- AWS mast (Lit), 32.8FT AGL, infringing transitional SFC by 23FT, PSN 740M FM RWY 12 SOT 111M right of RWY CL.

**METEOROLOGICAL INFORMATION PROVIDED**

- TAF CAT C, METAR/SPECI.
- AWIS FREQ 130.3 - Report faults to AD OPR.

**PHYSICAL CHARACTERISTICS**

12/30 123 75a PCN 27 / F / A / 1200 (174PSI) / T

WID 30 RWS 150

**AERODROME AND APPROACH LIGHTING**

RWY 12/30 LIRL AFRU+PAL 127.05

SDBY PWR AVBL

RWY 12/30 PAPI(1) AFRU+PAL 127.05 3.0 DEG54FT

SDBY PWR AVBL

RWY 12/30 PTBL(2)

BY PRIOR  
ARRANGEMENT

(1) Left side.

(2) 90 MIN PN.

- PAL Activation - allow for a 5 SEC delay for notification of successful activation before a second attempt.
- Main and SDBY PWR supplied by AD generators.

**OTHER LIGHTING**

- TWY LGT: Blue edge.
- SDBY PWR switchover time: 45 SEC.

**ATS AND AERODROME COMMUNICATION FACILITIES**

FIA MELBOURNE CENTRE

128.15 Circuit area

UNICOM FORTESCUE DAVE

127.05 (1)

FORREST UNICOM

- (1) Callsign "Fortescue UNICOM". AVBL for scheduled movements.

**LOCAL TRAFFIC REGULATIONS**

- ACFT ABV 5,700KG MTOW use RWY end 45M nodes for 180DEG turns.
- All traffic to access the APN via TWY A

3. Dual lead in lines on PRKG Bay 1. Lead in lines marked as 1 or 1A
  - a. ACFT to use lead in 1: B712
  - b. ACFT to use lead in 1A: A320, B738, GLEX, F100, DH8A, DH8C, Q400 and E120

### **FLIGHT PROCEDURES**

1. DEP RWY 12 left hand turn only as soon as practicable after TKOF. South bound TFC to intercept track overhead YDFD.
2. DEP ACFT to use RWY 30 in calm wind conditions.
3. All ACFT to call airborne on CTAF FREQ as soon as practicable after TKOF.

### **CTAF - AFRU 127.05**

### **ADDITIONAL INFORMATION**

1. Blasting occurs BTN 4.3NM and 13NM to SE and W of ARP BTW 125 and 273 DEG MAG.
2. Dust plumes may occur following blasting.
3. CAUTION: YCHK is in close proximity and the APCH/DEP tracks cross close to the ground. Due to terrain shielding, VHF contact with ACFT on or close to the ground at YCHK is not possible.

### **CHARTS RELATED TO THE AERODROME**

1. WAC 3229.
  2. Also refer to AIP Departure and Approach Procedures.
-