

CARNARVON

RWY	(CN)	TORA	TODA	ASDA	LDA
04	(3)	1619 (5312)	1679 (5508) (2.14%)	1619 (5312)	1619 (5312)
RWY 04 has non-standard approach surface - inner edge of APCH SFC 40M from RWY end.					
22	(3)	1619 (5312)	1679 (5508) (3.85%)	1619 (5312)	1619 (5312)
RWY 22 OBST fence 7FT AGL, 85M left of CL. TKOF GRAD to levee bank 6.8%. Slope 0.1% down to SW. RWY WID 30 RWS WID 150					
18	(1)	1140 (3740)	1200 (3937) (2%)	1140 (3740)	1140 (3740)
36	(1)	1140 (3740)	1200 (3937) (4.14%)	1140 (3740)	1140 (3740)
OBST fence 4FT AGL 28M N of RWS end. TKOF GRAD 4.7%. Slope 0.1% down to S. RWY WID 30 RWS WID 90					

SUPPLEMENTARY TAKEOFF DISTANCES

RWY04-	1344(4409)(1.6)	1556(5105)(1.9)			
RWY22-	1176(3858)(1.6)	1308(4291)(1.9)	1406(4613)(2.2)	1481(4859)(2.5)	1617(5305)(3.3)
RWY18-	1072(3517)(1.6)	1192(3911)(1.9)			
RWY36-	885(2904)(1.9)	983(3225)(2.2)	1057(3468)(2.5)	1185(3888)(3.3)	