

BALLARAT

RWY	(CN)	TORA	TODA	ASDA	LDA
05	(3)	1265 (4150)	1325 (4347) (4.63%)	1265 (4150)	1265 (4150)
			RESA dimensions 55M X 30M commences from RWY end.		
			RWY 05 S side transitional SFC infringed by tower and radio aerial.		
23	(3)	1265 (4150)	1325 (4347) (6.05%)	1265 (4150)	1265 (4150)
			RESA dimensions 150M X 30M commences from RWY end.		
			Slope 0.4% from centre down to ends. RWY WID 30 RWS WID 90		
13	(1)	568 (1863)	628 (2060) (2.05%)	568 (1863)	568 (1863)
31	(1)	568 (1863)	628 (2060) (1.38%)	568 (1863)	568 (1863)
			Slope 0.6% down to N. RWY WID 30 RWS WID 90		
18	(3)	1245 (4085)	1305 (4281) (2.49%)	1245 (4085)	1245 (4085)
			1. 3.33% OBST CLR APCH SFC LDG RWY 18 terminates at THR, not RWS end.		
			2. LDG RWY 18 - Unlit OBST fence 4.9FT ABV and 36M N of RWS end.		
			3. Transient OBST up to 17.6FT ABV and 57M S of RWS end is not taken into account in calculation of TODA GRAD and STODA.		
			4. OBST fence up to 6.5FT ABV and PARL to RWY, 78M E of RCL not taken into account in calculation of TODA GRAD and STODA.		
			5. Unlit OBST fence 8.2FT ABV, 32M S of RWS end not taken into account in calculation of TODA GRAD and STODA.		
36	(3)	1245 (4085)	1305 (4281) (3.43%)	1245 (4085)	1245 (4085)
			RESA dimensions 130M X 30M commences from RWY end.		
			OBST fences 4.2FT ABV and PARL to RWY, 77M E of RCL, and 3.8FT ABV and 87M W of RCL are not taken into account in calculation of TODA GRAD and STODA.		
			Slope 0.1% down to N. RWY WID 30 RWS WID 150 Graded 90		

SUPPLEMENTARY TAKEOFF DISTANCES

RWY05-	967(3173)(2.2)	1043(3422)(2.5)	1201(3940)(3.3)
RWY23-	875(2871)(1.6)	1001(3284)(1.9)	1115(3658)(2.2) 1211(3973)(2.5) 1311(4301)(3.3)
	1321(4334)(5.0)		
RWY18-	841(2759)(1.9)	1115(3658)(2.2)	
RWY36-	1208(3963)(2.5)	1294(4245)(3.3)	